

### General Information

Dimensions (mm)	320 (Dia.) x 113 (D)
Materials	Base & Diffuser: Polycarbonate (UV Stabilised) LED Array: Aluminium Substrate
Finish	White (RAL 9010)
Product Weight (Kg)	1
Ingress Protection	IP65
Impact Rating (IK)	08
Flammability Rating	UL94-V2
Mounting	Ceiling or Wall
Warranty (Years)	5
Battery Warranty (Years)	4

### Luminaire Output


Colour Temperature (K)	3000	4000	6000
Typical Luminous Flux (lm)	1250	1500	1400
Efficacy (lm/W)	69	83	87
Beam Angle (°)	107		
Emergency Luminous Flux (lm)	98	98	98
Colour Rendering Index (CRI)	>80		
LED Lifetime (L70) (Hours)	30,000		

### Emergency Backup Information


Self-Test Facility	Yes
Emergency Luminous Flux (lm)	98
Installation	Can be wired as maintained or non-maintained
Battery Specification	Li-Ion 2000mAh 3.7V
Minimum Duration (Hours)	3
Battery Warranty (Years)	4

### Supply & Power Information


Input Voltage & Frequency (V~ / Hz)	220-240 50/60
Safety Class	II
Surge Protection Installed	
Circuit Wattage (W)	18
LED Wattage (W)	16
Input Current (mA)	120
Power Factor	>0.95
Driver Information	Integrated
Operating Temperature (°C)	0 to +50
Maximum Critical Temperature (°C)	+80
Input Terminations	4 Pole Push-fit Terminals



3000



4000



6000

